Power Amplifier (360W) – LUCKY TONE

Description:

This range of amplifiers is designed for commercial and industrial grade public address applications. With efficient components, it delivers 360 to 660 watts of clean, reliable audio for the most demanding public address applications. Rugged and over-built to give years of dependable service, they are equipped with massive toroidal power transformers, extensive heatsinking and fan cooling, protective circuits such as over-temperature, short circuit, RFI, clip, overload and soft start.

Features:

- Flexible power rating of 360/460/660W
- Master Volume control in the front
- 100V, 70V and 4-16 Ohms transformer isolated speaker outputs
- Combination XLR/RCA Line In and Line Out connectors
- LED status indicators
- Speaker output short circuit protection

MODEL	**PA-360**
Rated Power Output	360W
Output Regulation	Less than 3 dB (no load to full load)
Output	775V, 0dB, XLR and phone jack
Frequency Response	60 – 16,000 Hz, +/- 3dB
THD	Less than 0.5% at 1kHz (1/3 Rated Power)
S/N Ratio	Better than 73dB
Slew Rate	15V/Us
Controls	Volume control and power switch
Cooling	Internal 12VDC fan, extensive heat sinking
Indicators	Power, Clip, Signal, Protect, and Temp LEDs
Protection	AC Fuse: 10A
	Current limiter, short circuit and thermal protection circuits
Power Consumption	485W
Power Requirement	220-240V AC, 50/60 Hz
Dimensions	89(H) x 483(W) x 366(D) mm
Built-in Dimensions	2U rack 19 inch
Carton Dimensions	185(H) x 520(W) x 435(D) mm
Net Weight	15.12kg
Gross Weight	16.76kg

Finish	Panel: steel plate, black
	Case: steel plate, black



